



<b>EKO-CUP S3</b>		<b>120</b>	<b>160</b>	<b>240</b>	<b>320</b>	<b>400</b>	<b>460</b>	<b>530</b>	<b>600</b>
<b>Toplinski učin</b>	(kW)	80-120	120-160	160-240	240-320	320-400	400-460	460-530	530-600
<b>Sadržaj vode u kotlu</b>	(l)	175	240	320	360	590	705	825	950
<b>Ukupna masa kotla</b>	(kg)	357	505	648	798	1003	1118	1248	1378
<b>Max. radna temperatura</b>	(°C)	90							
<b>Max. radni pretlak</b>	(bar)	3 ili 6							
<b>Promjer/visina (l) dimnjače</b>	(mm)	180/700	200/790	200/790	250/900	250/970	250/970	300/1050	300/1050
<b>Otvor za plamenik</b>	$\phi$ (mm)	130	130	170	170	170	220	220	220
<b>Otpor ložišta</b>	(mbar)	1,7	2,5	2,6	2,8	3,5	4,0	4,3	4,9
<b>Polazni/povratni vod kotla (NP6)</b>		R 2"	DN 50	DN 65	DN 80	DN 80	DN 80	DN 80	DN 100
<b>Punjenje/pražnjenje</b>	(R)	3/4"	3/4"	3/4"	3/4"	1"	1"	1"	1"
<b>Sigurnosni vod</b>	(R)	1"	5/4"	5/4"	6/4"	6/4"	6/4"	6/4"	6/4"
<b>Temp. dimnih plinova</b>	(°C)	185 - 190							
<b>Duljina tijela kotla A</b>	(mm)	1400	1400	1870	1870	1915	2215	2215	2355
<b>Širina tijela kotla B</b>	(mm)	780	950	950	1050	1150	1150	1200	1250
<b>Visina tijela kotla C</b>	(mm)	970	1110	1110	1225	1355	1355	1450	1455
<b>Ukupna duljina D</b>	(mm)	1400	1400	1870	1870	1915	2215	2215	2355
<b>Ukupna širina E</b>	(mm)	780	950	950	1050	1150	1150	1200	1250
<b>Ukupna visina F</b>	(mm)	1070	1195	1195	1305	1405	1405	1485	1505
<b>Visina G</b>	(mm)	910	1040	1040	1150	1250	1250	1325	1350
<b>Visine (H / K)</b>	(mm)	380/170	440/170	440/170	440/180	450/185	450/185	480/185	480/185