



## EKO-CUP M3 Bg

18

25

35

50

65

80

Toplinski učin	(kW)	15-18	18-25	25-35	35-50	50-65	65-80
Sadržaj bojlera PTV	(l)	-	- / 80	- / 80	- / 80	- / 80	- / 120
Količina PTV (45°C)	(l/min)	-	- / 8,8	- / 8,8	- / 8,8	- / 8,8	- / 12,5
Sadržaj vode u kotlu	(l)	48	54 / 97	80 / 98	85 / 118	105 / 143	130 / 170
Masa kotla	(kg)	105	117 / 195	147 / 220	168 / 236	206 / 275	235 / 315
Promjer/visina (E) dimnjače	(mm)	130/440	130/434	130/490	150/515	160/580	160/580
Otvor za plamenik	φ(mm)	100	100	100	100	110	110
Potlak dimnjaka	(Pa)	8	10	12	14	16	18
Polazni/povratni vod	(R)	1"	1"	5/4"	5/4"	6/4"	6/4"
Temp. dimnih plinova	(°C)	170	170	170	170	170	170
Max. radna temperatura	(°C)	90	90	90	90	90	90
Max. radni pretlak	(bar)	2,5	2,5	2,5	2,5	2,5	2,5
Ukupna duljina A	(mm)	1175	1275	1275	1275	1275	1315
Ukupna širina B	(mm)	500	500	580	630	690	690
Ukupna visina C	(mm)	790	790	860	890	960	960 / 1185
Visine D	(mm)	215	215	230	250	250	250
Visina F	(mm)	595	595	660	700	760	760
Visina G	(mm)	-	- / 687	- / 755	- / 800	- / 865	- / 865
Visina H	(mm)	-	- / 777	- / 845	- / 890	- / 955	- / 955
Visina I	(mm)	-	- / 867	- / 935	- / 980	- / 1045	- / 1045
Visina J	(mm)	-	- / 1006	- / 1080	- / 1120	- / 1180	- / 1180